

MANTSINEN 60 MHC



**Material handling machine
Mobile harbour crane**



Mantsinen 60 MHC

Technical specifications

Front equipment		
Max. horizontal reach	21 m	69'
Lifting capacity	Approx. 12 t / 10 m	6.5 t / 16 m

Engine

Type	Isuzu AH-6W41XYA-01	
Power	260 kW	353 hp
Number of cylinders	6	
Displacement	15.7 l	957 cu.in

Undercarriage

Height	2 m to 4 m	6'7" to 13'1"
Wheelbase	3.700 mm	12'
Axles	80 ton axles with planetary reductions	
Drive speed	Max. 10 km/h	6 mph

Hydraulic system

Oil flow	2 x 367 l/min	2 x 97 gpm U.S.
Working pressures	Equipment 320 bar	4 500 PSI
	Swing 280 bar	4 000 PSI
	Drive 350 bar	5 000 PSI
Max. swing speed	9 rpm	

Cab elevator N2-3600 (option)

Horizontal movement	Max. 6.4 m (21') from original position
Vertical movement	Max. 8.6 m (28'3") operator eye level

Weight

With undercarriage height 2.5 m, cab elevator, without attachment		
	63.000 kg	139 000 lbs

Refill capacities

Hydraulic system	560 l	148 gal U.S.
Fuel tank	725 l	191 gal U.S.

Illustrated machines can have optional equipment.
Specifications subject to change without prior notice.



Mantsinen Oy
Välikankaantie 3
FI-80400 Ylämylly
FINLAND

Your dealer:

Tel +358 13 252 5500
Fax +358 13 252 5555
www.mantsinen.com