

# THE LATEST GENERATION WX WHEELED EXCAVATORS



Wheeled excavators		WX150	WX170		WX200
Weight	kg	13.5 à 16.5 t	15.8 à 19.3 t		19 à 21.2 t
Chassis		P, PL, P2A, P2AL, P4A	P, PL, P2A, P2AL, P4A		P2A, P2AL, P4A
<b>ENGINE</b>					
Engine type		4TA-390	6T-590		6TA-590
Manufacturer		CASE	CASE		CASE
Net power (CEE 80/1269)	kW / hp	76 kW - 102 hp	90 kW - 120.6 hp		113 kW - 151.5 hp
Engine rpm	rpm	2000	2000		2000
Displacement	L	3,92	5,88		5,88
Auto iddle		Auto or manuel	Auto or manuel		Auto or manuel
<b>HYDRAULIC</b>					
Electronic system		ECOPOWER	ECOPOWER		ECOPOWER
Modes		MAXI, ECO, LIFT	MAXI, ECO, LIFT		MAXI, ECO, LIFT
Autopowerboost		Automatic	Automatic		Automatic
Pumps flow	L/mn	201 + 44	320 + 56		320 + 88
Attachment pressure	bar	350/380	350/380		350/380
Swing speed	rpm	7.7	7.7		8.5
Road speed travel	km/h	0 à 25	0 à 25.3		0 à 24.5
Working speed travel	km/h	0 à 7.5	0 à 7.6		0 à 7.3
<b>PERFORMANCES</b>					
Mono boom	m	4.3	4.8	5.2	4.8 5.4
Dipper	m	2.1	2.1	2.1	2.5 2.5
Maxi digging depth	m	4.75	4.95	5.35	5.35 5.9
Maxi loading height	m	6	9.15	9.45	9.7 10.15
Maxi reach	m	7.95	8.55	9	9 9.6
Breakout force	daN	10600	13400	13400	16150 16150
Digging force	daN	6300	9650	9650	10650 10650
Lift 6 m ± 3 m 360° (P2AL)	kg	3500	4100	4000	4150 3900
Lift 6 m ± 3 m axe (P2AL°)	kg	4400*	4750*	4900*	5300* 5400*

**CASE**

## REMARKABLE PERFORMANCE

- **New electronic management system with «BUSCAN» connections**
- **Autopowerboost**
- **«LIFT» mode for handling**
- «Inching» speed programmer
- Axial locking mode - auto or manual
- **Independent cooling system**

## HIGH LEVEL OF COMFORT & SAFETY

- **New «high visibility» cab with new windscreen lifting system**
- **Glass roof with integrated sun shield**
- **LED/LCD instrument panel**
- **Working area lighting**
- **Automatic parking brake**
- **Coded anti-theft system**
- **Quick coupler unlocking safety system**
- **«Safety» travel position**
- Independent dozer blade and stabilisers
- Forward / reverse travel control from the control levers
- «Air» suspension comfort seat, with reel-type safety belt (depending on country)
- Boom and dipper safety valves are standard (depending on country)
- Chassis configurations - to provide the best stability - always

## UNIQUE VERSATILITY

- *Modular chassis (5 versions)*
- *Choice of 2 types of stabiliser*
- *Parallelogram dozer blade*
- *Large choice of attachments (booms, dippers, buckets, clamshells, quick couplers, hammers, grabs)*

## EASY MAINTENANCE

- **New toolbox-type «steps»**
- *Access walkway over the whole width of the machine*
- *Exceptional accessibility to the filters, fluid levels, greasing points and the main components*
- *«Ecological» engine drain valve*

**WX150 - WX170 - WX200**