



SKR10: TEN TONNE ROTARY TIPPING DUMPER

Capacities:		Engine type:		
Payload capacity – tonnes	10	lveco N45 MNTD 94kW @ 2300rpm		4485cc
Liquid capacity — Itr	2955			
Struck capacity — ltr	3732	Transmission:		
Heaped capacity — Itr	5170	Powershuttle transmission, 4 speeds forward and reverse with torque converter. Heavy duty drive train.		
Dimensions:				
A = overall length – mm	5047	Axles and brakes:		
B = overall height - ROPS up — mm	3246	Heavy duty double reduction axles with fully floating half		
C = overall height - ROPS down — mm	2308	shafts. Totally enclosed oil immersed disc brakes.		
D = overall height - skip tipped — mm	3867			
E = prow height — mm	2026	Wheels and tyres:		
F = tipped prow height — mm	1014	500/60 - 22.5 High floatation tyres		16 ply
G = side loading height — mm	2164	200,00 Zzio ingii nodidatori tyroo		10 p.y
H = wheel base – mm	2650	Tank capacities:		
I = ground clearance — mm	440	68 ltr fuel tank	40 ltr hydraulic tank	
Overall width – mm	2621	oo iii idoi taiik	10 10 11	yaraano tam
Width over tyres – mm	2430	Road speed mph/kph:		
Outer turning circle – metres	13.2	1st gear:	3.0	4.8
		2nd gear:	4.9	7.8
Weight:		3rd gear:	9.2	14.7
Unladen weight – kg (with ROPS and full tanks)	5139	4th gear:	16.7	26.8

Barford Construction Equipment Houghton Road Grantham Lincolnshire NG31 6JE Tel +44 (0)1476 515510 Fax +44 (0)1476 515450 www.barforddumpers.co.uk