



SX5000: FIVE TONNE FORWARD TIPPING DUMPER

Capacities:		Engine type:		
Payload capacity – tonnes	5	lveco N45MSSX00 74kW @ 230	00rpm	4485cc
Liquid capacity — Itr	1710			
Struck capacity — Itr	2097	Transmission:		
Heaped capacity – Itr	2914	Powershuttle transmission, 4 speeds forward and reverse with torque converter. Heavy duty drive train.		
Dimensions:				
A = overall length - mm	4252	Axles and brakes:		
B = overall height - ROPS up - mm	3070	Heavy duty double reduction axles with totally enclosed oil		
C = overall height - ROPS down - mm	1190	immersed disc brake. Transmission parking brake (front only)		
D = overall height - skip tipped - mm	2515			
E = prow height – mm	1604	Wheels and tyres:		
F = tipped prow height - mm	345	12.5/80 - 18		16 ply
G = side loading height – mm	1730			
H = wheel base - mm	2400	Tank capacities:		
I = ground clearance — mm	320	68 ltr fuel tank	40 ltr hydraulic tank	
Overall width – mm	2163			
Width over tyres – mm	2090	Road speed mph/kph:		
Outer turning circle – metres	12.2	1st gear:	3.1	5.0
		2nd gear:	5.2	8.3
Weight:		3rd gear:	9.5	15.2
Unladen weight – kg (with ROPS and full tanks)	4200	4th gear:	17.6	28.1