



## **SX8000: EIGHT TONNE FORWARD TIPPING DUMPER**

Capacities:		Engine type:		
Payload capacity – tonnes	8	lveco N45MSSX00 74kW @ 230	0rpm	4485cc
Liquid capacity — ltr	2052			
Struck capacity — Itr	2942	Transmission:		
Heaped capacity – ltr	3776	Powershuttle transmission, 4 speeds forward and reverse		
		with torque converter. Heavy d	uty drive train.	
Dimensions:				
A = overall length - mm	4267	Axles and brakes:		
B = overall height - ROPS up - mm	3158	Heavy duty double reduction axles with totally enclosed oil		
C = overall height - ROPS down - mm	2140	immersed disc brake. Transmission parking brake (front only)		
D = overall height - skip tipped — mm	????			
E = prow height – mm	1656	Wheels and tyres:		
F = tipped prow height - mm	????	18.0 - 19.5		16 ply
G = side loading height — mm	1857			
H = wheel base - mm	2400	Tank capacities:		
I = ground clearance — mm	430	68 ltr fuel tank	40 ltr hydraulic tank	
Overall width – mm	2495			
Width over tyres – mm	2310	Road speed mph/kph:		
Outer turning circle – metres	12.4	1st gear:	3.0	4.8
		2nd gear:	4.9	7.8
Weight:		3rd gear:	9.2	14.7
Unladen weight – kg (with ROPS and full tanks)	4388	4th gear:	16.7	26.8