

CASE FULL LINE CONSTRUCTION EQUIPMENT

CASE
PROFESSIONAL PARTNER





CUSTOMER SUPPORT

The Case dealer: Your professional partner

World-class construction equipment is just the start with Case. Consider your Case dealer your partner to find the right options for you to meet your job demands, including maintenance options, financing, attachments and the right machine size.

Case dealers help you maximize machine uptime — and profit. From high-tech tools designed to track equipment and manage a fleet, to service solutions performed right on the job site, Case dealers take the worry out of managing equipment.

Case dealers stand behind the equipment they sell with the strength of factory-trained technicians, a global parts network and outstanding warranties. To get through those high-demand projects, you can rely on your Case dealer for complete purchase, lease and rental solutions.

Your local Case dealer offers flexible financing options, leasing packages and insurance services to protect your investment.

You need more than great equipment. Case dealers deliver.





RESOURCES FOR YOUR BUSINESS

Case Care for maintenance needs

Imagine having experienced, factory-trained service technicians performing all the routine maintenance on your equipment, precisely to spec and right on schedule. Even better, think of how much extra time and peace of mind you would have if this professional service happened without you ever having to hire a service crew, find parts or crack open service manuals.

It can all happen with Case Care, the convenient prepaid maintenance plan from Case.

With Case Care, your local Case dealer handles all the scheduled maintenance on a contracted machine for a specific period of time. The agreement can be customized to fit just about any need and payment option. And because your work is being performed by experienced Case technicians, there's an added dimension to routine maintenance — the ability to spot trouble early and fix the problem before it leads to costly, unscheduled downtime and repairs.

In addition to superior quality service without the headaches of having to “do it yourself,” Case Care makes it easy to finance your scheduled maintenance. You can combine your Case Care payment with the monthly payment on your machine. And Case Care does not increase the down payment amount.

You can also purchase Case Care on your existing fleet by charging it to your commercial revolving account. You get two-year finance terms with no interest and no money down. There are no worries about tying up your credit line, either: your Case financial professionals created a fast and easy process to review accounts for credit line increases to accommodate your Case Care agreement.

Talk to your Case dealer today about Case Care and valuable options such as GlobalTRACS®, a fleet management communications system, and SYSTEMGARD® lubrication analysis. They can all work together to simplify fleet management and maintenance.

Case financing support from CNH Capital

Whether you want to purchase new or used equipment, lease, or rent, your Case dealer can design a plan through CNH Capital to suit your individual business needs.

A wide range of plans, including revolving credit lines for parts, service and repairs, offer very competitive rates and maximum flexibility in payment schedules to match your cash flow. With our flexible protection plan, you can even choose equipment coverage based on seasonal business cycles. Ask your Case dealer about the many other attractive financial services available to help keep your business productive — and profitable.



LOADER BACKHOES

M SERIES 2

580M

Net Horsepower
76 (56.7 kW)
Operating Weight
16,000 lb. (7257 kg)
Digging Depth
14 ft. 3 in. (4.34 m)
18 ft. 3 in. (5.56 m) – Extendahoe

580M turbo

Net Horsepower
80 (60 kW)
Operating Weight
16,000 lb. (7257 kg)
Digging Depth
14 ft. 3 in. (4.34 m)
18 ft. 3 in. (5.56 m) – Extendahoe

580 Super M

Net Horsepower
90 (67 kW)
Operating Weight
17,000 lb. (7711 kg)
Digging Depth
14 ft. 5 in. (4.39 m)
18 ft. 3 in. (5.56 m) – Extendahoe

580 Super M +

Net Horsepower
90 (67 kW)
Operating Weight
18,000 lb. (8165 kg)
Digging Depth
14 ft. 5 in. (4.39 m)
18 ft. 3 in. (5.56 m) –
Extendahoe

590 Super M

Net Horsepower
98 (73 kW)
Operating Weight
19,500 lb. (8845 kg)
Digging Depth
16 ft. 4 in. (4.97 m)
20 ft. 4 in. (6.19 m) –
Extendahoe

Standard Equipment

Power Train
4F-4R power shuttle (synchromesh)
Rear drive axle – outboard planetary
Electro-hydraulic differential lock
Torque converter
Loader
Single lever control with self-leveling
and return-to-dig
Brakes
Hydraulic actuated wet disk, self-adjusting
Backhoe
Pilot Controls (Optional)

TRACTOR LOADER

570M XT

Net Horsepower
73 (54 kW) – natural aspiration
80 (60 kW) – turbocharged
SAE Lift Capacity
6,500 lb. (2951 kg)
Operating Weight
12,000 lb. (5453 kg)

Standard Equipment

Power Train
4F-4R power shuttle (synchromesh)
Rear drive axle – outboard planetary
Electro-hydraulic differential lock
Torque converter
Loader
Single lever control with self-leveling
and return-to-dig
Electric clutch cut-out
Brakes
Hydraulic actuated wet disk, self-adjusting



ROUGH TERRAIN FORKLIFTS



585G

Net Horsepower
73 (54 kW)
Operating Weight
12,600 lb. (5715 kg)
Lift Capacity
5,000 lb. (2268 kg)

586G

Net Horsepower
73 (54 kW)
Operating Weight
13,750 lb. (6237 kg)
Lift Capacity
6,000 lb. (2722 kg)

Standard Equipment

Transmission
4F-4R power shuttle (synchromesh)
Differential lock
Torque converter
Brakes
Hydraulic wet disc brakes, self-adjusting
Mast Features
3 spool mast control
6 inch (15 cm) mast sideshift

588G

Net Horsepower
73 (54 kW)
Operating Weight
15,750 lb. (7144 kg)
Lift Capacity
8,000 lb. (3629 kg)



SKID STEERS

COMPACT RANGE

410

Net Horsepower
49 (37 kW)
SAE Operating Load
1,500 lb. (681 kg)
Operating Weight
5,483 lb. (2488 kg)
Loader Linkage
Radial design

420

Net Horsepower
56 (42 kW)
SAE Operating Load
1,750 lb. (794 kg)
Operating Weight
5,813 lb. (2637 kg)
Loader Linkage
Radial design

430

Net Horsepower
74 (55.2 kW)
SAE Operating Load
2,000 lb. (908 kg)
Operating Weight
6,875 lb. (3119 kg)
Loader Linkage
Radial design

440

Net Horsepower
82 (61.2 kW)
SAE Operating Load
2,200 lb. (998 kg)
Operating Weight
6,980 lb. (3167 kg)
Loader Linkage
Radial design

HEAVY RANGE

435

Net Horsepower
72 (54 kW)
SAE Operating Load
2,300 lb. (1043 kg)
Operating Weight
6,830 lb. (3098 kg)
Loader Linkage
Vertical lift

445

Net Horsepower
74 (55.2 kW)
SAE Operating Load
2,500 lb. (1134 kg)
Operating Weight
7,677 lb. (3482 kg)
Loader Linkage
Vertical lift

450

Net Horsepower
82 (61.2 kW)
SAE Operating Load
2,450 lb. (1111 kg)
Operating Weight
8,830 lb. (4005 kg)
Loader Linkage
Radial design
Mechanical self leveling

465

Net Horsepower
82 (61.2 kW)
SAE Operating Load
3,000 lb. (1364 kg)
Operating Weight
8,910 lb. (4042 kg)
Loader Linkage
Vertical lift

Standard Equipment

Operator's Environment

Tilt forward ROPS/FOPS
Rear window

Hydraulics

Auxiliary hydraulics

Brakes

Spring applied hydraulic release
(SAHR) parking brake

COMPACT TRACK LOADERS

445CT

Net Horsepower
74 (55.2 kW)
SAE Operating Load
2,500 lb. (1134 kg)
Operating Weight
9,815 lb. (4452 kg)
Loader Linkage
Vertical lift

450CT

Net Horsepower
82 (61.2 kW)
SAE Operating Load
2,700 lb. (1225 kg)
Operating Weight
10,915 lb. (4951 kg)
Loader Linkage
Radial design
Mechanical self leveling

Standard Equipment

Operator's Environment

Tilt forward ROPS/FOPS
Rear window

Hydraulics

Auxiliary hydraulics

Brakes

Spring applied hydraulic release
(SAHR) parking brake



CRAWLER DOZERS

550H

Net Horsepower
67 (50 kW) – natural aspiration
70 (52 kW) – turbocharged
Operating Weight
LT – 14,317 lb. (6500 kg)
LGP – 14,960 lb. (6792 kg)

1150H

Net Horsepower
119 (89 kW)
Operating Weight
LT – 25,300 lb. (11 486 kg)
LGP – 27,060 lb. (12 285 kg)

650K SERIES 2

Net Horsepower
75 (56 kW)
Operating Weight
LT – 18,000 lb. (8244 kg)
LGP – 19,400 lb. (8813 kg)

750K SERIES 2

Net Horsepower
84 (63 kW)
Operating Weight
LT – 18,900 lb. (8569 kg)
LGP – 20,200 lb. (9157 kg)

850K SERIES 2

Net Horsepower
96 (72 kW)
Operating Weight
LT – 19,600 lb. (8900 kg)
LGP – 20,700 lb. (9402 kg)

550H & 1150H

Standard Equipment

Transmission

4F-4R speed modulated, powershift with
power turn transmission

1650K

Net Horsepower
140 (104 kW)
Operating Weight
LT – 33,750 lb. (15 323 kg)
LGP – 35,700 lb. (16 208 kg)

1850K

Net Horsepower
LT, XLT – 180 (134 kW)
LGP – 194 (145 kW)
Operating Weight
LT – 43,750 lb. (19 862 kg)
XLT – 45,415 lb. (20 600 kg)
LGP – 48,500 lb. (22 019 kg)

650K, 750K & 860K SERIES 2

Standard Equipment

Drive Train

Dual path infinitely variable
hydrostatic transmission
Single lever transmission control
Counter rotation – available with full
left or right steering



1650K & 1850K

Standard Equipment

Drive Train

Powershift transmission with 3F-3R speeds
Single lever joystick control with forward/reverse
Slider switch for up/down gear shifts

WHEEL LOADERS

D SERIES

521D

Net Horsepower
110 (82 kW)
Operating Weight
Z-bar – 22,109 lb. (10 028 kg)
XT – 23,938 lb. (10 858 kg)
Bucket Capacity
2.5 cu. yd. (1.91 m³)

621D

Net Horsepower
136 (101 kW)
Operating Weight
Z-bar – 26,083 lb. (11 831 kg)
XT – 27,877 lb. (12 645 kg)
XR – 26,364 (11 958 kg)
Bucket Capacity
3.0 cu. yd. (2.3 m³)

721D

Net Horsepower
170 (127 kW)
Operating Weight
Z-bar – 30,644 lb. (13 900 kg)
XT – 31,574 lb. (14 322 kg)
Bucket Capacity
3.5 cu. yd. (2.68 m³)

C SERIES

821C

Net Horsepower
186 (139 kW)
Operating Weight
37,901 lb. (17 191 kg)
Bucket Capacity
4.0 cu. yd. (3.05 m³)

921C

Net Horsepower
248 (185 kW)
Operating Weight
50,621 lb. (22 961 kg)
Bucket Capacity
5.0 cu. yd. (3.82 m³)

Standard Equipment

- Engine**
Hydraulically driven fan w/guard
- Drive Train**
Front/rear limited slip differentials
- Transmission**
Computer controlled, full-power, proportional shifting
Fully automatic programmable gear selection
On board diagnostics with fault code retrieval
- Loader System**
Two variable flow piston pumps
Automatic return-to-dig, height control and return-to-travel
Single lever/two spool loader control
- Brakes**
Outboard mounted, wet disc hydraulic brakes
Switch actuated, spring applied, hydraulic release parking brake



COMPACT WHEEL LOADERS

D SERIES 2

21D

Net Horsepower
51 (38 kW)
Operating Weight
9,818 lb. (4453 kg)
Bucket Capacity
0.9 cu. yd. (0.688 m³)

221D

Net Horsepower
57.5 (4.5 kW)
Operating Weight
11,793 lb. (5349 kg)
Bucket Capacity
1.18 cu. yd. (0.902 m³)

321D

Net Horsepower
71 (53.5 kW)
Operating Weight
13,028 lb. (5909 kg)
Bucket Capacity
1.31 cu. yd. (1.0 m³)

Standard Equipment

- Drive Train**
Front limited slip differential
- Transmission**
2-speed hydrostatic transmission
Single lever shift control
High Travel Speed (HTS) up to 21 mph (33.8 kph) (optional on 221D & 321D)
- Loader System**
Automatic return-to-dig
Single lever/two spool loader control
Hydraulic coupler
- Brakes**
Dry disc hydraulic brakes
- Other**
Front & rear tie down points



EXCAVATORS

CX SERIES

CX80

Net Horsepower
52 (39.1 kW)
Operating Weight
18,409 lb. (8350 kg)
Digging Depth – 8 ft. bottom
12 ft. 5 in. (3.73 m)

CX130

Net Horsepower
110 (82 kW)
Operating Weight
27,057 lb. (12 273 kg)
Digging Depth – 8 ft. bottom
17 ft. 6 in. (5.33 m)

CX160

Net Horsepower
110 (82 kW)
Operating Weight
36,226 lb. (16 431 kg)
Digging Depth – 8 ft. bottom
19 ft. 5 in. (5.92 m)

CX210

Net Horsepower
153 (114 kW)
Operating Weight
44,000 lb. (19 976 kg)
Digging Depth – 8 ft. bottom
21 ft. 5 in. (6.53 m)

CX240

Net Horsepower
180 (134 kW)
Operating Weight
53,240 lb. (24 149 kg)
Digging Depth – 8 ft. bottom
22 ft. 4 in. (6.8 m)

CX290

Net Horsepower
190 (142 kW)
Operating Weight
64,720 lb. (29 356 kg)
Digging Depth – 8 ft. bottom
22 ft. 10 in. (6.96 m)

CX330

Net Horsepower
275 (205 kW)
Operating Weight
78,043 lb. (35 400 kg)
Digging Depth – 8 ft. bottom
23 ft. 7 in. (7.19 m)

CX460

Net Horsepower
316 (236 kW)
Operating Weight
101,250 lb. (45 926 kg)
Digging Depth – 8 ft. bottom
24 ft. 10 in. (7.57 m)

CX800

Net Horsepower
444 (331 kW)
Operating Weight
175,260 lb. (79 496 kg)
Digging Depth – 8 ft. bottom
28 ft. 1 in. (8.56 m)

STANDARD EQUIPMENT

Operator's Environment
Automatic climate control system
Undercarriage
Sealed outer flanged rollers

Track Drive
Two speed travel
Hydraulics
Two variable flow piston pumps



MINIMUM SWING RADIUS

CX75

Net Horsepower
52 (39 kW)
Operating Weight
16,933 lb. (7680 kg)
Digging Depth
12 ft. 6 in. (3.81 m)

CX135

Net Horsepower
88 (66 kW)
Operating Weight
29,280 lb. (13 281 kg)
Digging Depth
17 ft. 3 in. (5.26 m)

CX225

Net Horsepower
141 (105 kW)
Operating Weight
51,460 lb. (23 341 kg)
Digging Depth
21 ft. 5 in. (6.53 m)

Standard Equipment

Operator's Environment
Air conditioning
Undercarriage
Front track guides
Track Drive
Two speed travel
Hydraulics
Two variable flow piston pumps



COMPACT

CX14

Net Horsepower
11.9 (8.87 kW)
Operating Weight
3,240 lb. (6193 kg)
Digging Depth
6 ft. 11 in. (2.1 m)

CX27B

Net Horsepower
21.3 (15.9 kW)
Operating Weight
5,556 lb. (2570 kg)
Digging Depth
9 ft. 2 in. (2.79 m)

CX31B

Net Horsepower
28.4 (21.2 kW)
Operating Weight
6,790 lb. (3080 kg)
Digging Depth
9 ft. 2 in. (2.79 m)

CX36B

Net Horsepower
28.4 (21.2 kW)
Operating Weight
8,069 lb. (3660 kg)
Digging Depth
10 ft. 11 in. (3.35 m)

CX50B

Net Horsepower
40.8 (30.4 kW)
Operating Weight
10,383 lb. (4710 kg)
Digging Depth
11 ft. 9 in. (3.59 m)

Standard Equipment

Operator's Environment
Control pattern selector valve
Undercarriage
Rubber tracks
Track Drive
Two speed travel

Hydraulics
Two main hydraulic pumps
Variable displacement (not available on CX14)
One swing pump (not available on CX14)
One pilot pump



COMPACTION

DV SERIES - DUAL DRUM ROLLER

DV201

Horsepower
27 (20 kW)
Operating Weight
5,500 lb. (2497 kg)
Drum Width
39.4 in. (100 cm) wide
by 29 in. (73.6 cm)
diameter

DV202

Horsepower
27 (20 kW)
Operating Weight
5,900 lb. (2679 kg)
Drum Width
47.2 in. (120 cm) wide
by 29 in. (73.6 cm)
diameter

DV204

Horsepower
38 (27.5 kW)
Operating Weight
7,700 lb. (3496 kg)
Drum Width
51.2 in. (130 cm) wide
by 29.4 in. (74.6 cm)
diameter

Standard Equipment

Operator's Environment

Single lever speed/direction
and vibration ON/OFF control

Transmission

Hydrostatic drive
Variable displacement axial piston type
drive pump

Drum

Dual frequency vibration
Dual drum vibration

Brakes

Hydrostatic service brakes



SV SERIES - SINGLE DRUM ROLLER

SV208

Gross Horsepower
100 (75 kW)
Operating Weight
15,741 lb. (7140 kg)
Drum Width
66 in. (1.7 m) wide by
51 in. (1.3 m) diameter

SV210

Gross Horsepower
100 (75 kW)
Operating Weight
19,445 lb. (8820 kg)
Drum Width
66 in. (1.7 m) wide by
51 in. (1.3 m) diameter

SV212

Gross Horsepower
148 (110 kW)
Operating Weight
24,442 lb. (11 097 kg)
Drum Width
87 in. (2.2 m) wide by
59 in. (1.5 m) diameter

SV216

Gross Horsepower
148 (110 kW)
Operating Weight
31,553 lb. (14 325 kg)
Drum Width
87 in. (2.2 m) wide by
59 in. (1.5 m) diameter

Standard Equipment

Transmission

4-speed drive selection system
Hydrostatic rear drive wheels with
Interlock Control

Drum

Dual frequency vibration
Dual amplitude
Auto-vibration control

Brakes

Hydraulically actuated wet disc
brakes, self-adjusting



MOTOR GRADERS

845

Net Horsepower
140 (104 kW)
Operating Weight
29,777 lb. (13 535 kg)

865

Net Horsepower
169 (126 kW)
Operating Weight
32,077 lb. (14 550 kg)

865 DHP

Net Horsepower (Dual HP)
170 (127 kW)
200 (149 kW)
Operating Weight
32,077 lb. (14 550 kg)

885

Net Horsepower
200 (149 kW)
Operating Weight
37,950 lb. (17 250 kg)

Standard Equipment

Drive Train

Differential lock

Hydraulics

Closed center, load sensing hydraulic system
Eight hydraulic diagnostic quick couplers

Transmission

Direct drive countershaft powershift
transmission with inching pedal
Transmission onboard diagnostics

Operator's Environment

Cloth suspension seat
Air conditioning, heater/
defroster, pressurizer



ARTICULATED TRUCKS

325

Net Horsepower
248 (185 kW)
Rated Payload
50,706 lb. (22 999 kg)
Dump Capacity
17.4 cu. yd. (13.3 m³)

330

Net Horsepower
300 (224 kW)
Rated Payload
59,525 lb. (27 000 kg)
Dump Capacity
21.6 cu. yd. (16.5 m³)

335

Net Horsepower
380 (284 kW)
Rated Payload
69,445 lb. (31 500 kg)
Dump Capacity
26.2 cu. yd. (20 m³)

340

Net Horsepower
426 (318 kW)
Rated Payload
79,366 lb. (26 000 kg)
Dump Capacity
28.8 cu. yd. (22 m³)

Standard Equipment

Transmission

6F-3R speeds
Lock up in all gears
Outboard planetary
Front/rear limited slip differentials

Operator's Environment

Air conditioning
Left and right outside mirrors
Air suspension driver's seat w/3 in. (7.62 cm)
retractable seat belt
Passenger seat

ATTACHMENTS

Case Construction Equipment works with a variety of attachments, giving you additional production for your investment. They can be adapted for work in a wide range of tough applications, including road construction, recycling, waste management, as well as a wide range of job environments like home construction, utility work and landscaping.

Our well-designed buckets boost your productivity and last a long time, deserving of special recognition.

The bucket angle slopes smoothly to move the material toward the back of the bucket to begin the boiling action. The flat part at the top of the bucket helps an operator determine proper alignment.

For improved wear in harsh conditions, skid plates cover the entire depth of the bucket and replaceable heel plates are beveled to prevent material build-up and accelerated wear of the bottom of the bucket.

A reversible bolt-on cutting edge extends past the edge of the bucket for improved penetration. The welded cutting edge has the same angle as the bolt-on edge so material moves smoothly into the bucket. Bolt-on teeth and segments are also available.

From the general-purpose bucket to the 4-IN-1 or special side-dump bucket, there's one that best meets your equipment needs.

And quick tool changes mean there's more time to work. The Case quick-change coupling systems let you change a variety of attachments fast, with easy mounting and dismounting. Our attachments are designed to specifically work with Case equipment, delivering powerful performance matched to your machine's specifications.

Whether the task involves lifting, digging, spreading or cutting, Case attachments can help your equipment finish the job.



Hydraulic Quick Coupler



Angle Broom



Auger



Cold Planer



Landscape Rake



Tree Spade



Pick-up Broom



4-in-1° Bucket



Jib Booms



Scrap Grapple Buckets



Backhoe



Mini-hoe



Side Dump Bucket



Boom Arm



Pallet Forks



Snow Blowers



Concrete Chute



Pipe Forks



Stump Grinder



Hammer



Preparator



Trencher

More available attachments:

- Concrete bucket
- Concrete claw
- Dozer blade
- Harley rake
- Hopper broom
- Post driver
- Scrap grapple
- Snow push
- Snow blade

**CASE CONSTRUCTION EQUIPMENT
LOADER BACKHOES**

580M/580M turbo/580 Super M/580 Super M+/590 Super M

TRACTOR LOADERS

570M XT

ROUGH TERRAIN FORKLIFTS

585G/586G/588G

SKID STEERS

410/420/430/435/440/445/450/465

COMPACT TRACK LOADERS

445CT/450CT

CRAWLER DOZERS

550H/1150H 650K/750K/850K/1650K/1850K

COMPACT WHEEL LOADERS

21D/221D/321D

WHEEL LOADERS

521D/621D/721D 821C/921C

COMPACT EXCAVATORS

CX14/CX27B/CX31B/CX36B/CX50B

MSR EXCAVATORS

CX75/CX135/CX225

EXCAVATORS

CX80/CX130/CX160/CX210/CX240/CX290/CX330/CX460/CX800

MOTOR GRADERS

845/865/865DHP/885

COMPACTION

DV201/DV202/DV204 SV208/SV210/SV212/SV216

ARTICULATED TRUCKS

325/330/335/340

NOTE: All engines meet current EPA emission regulations.

NOTE: All specifications are stated in accordance with SAE Standards or Recommended Practices, where applicable.

IMPORTANT: CNH America LLC reserves the right to change these specifications without notice and without incurring any obligation relating to such change. Availability of some models and equipment builds vary according to the country in which the equipment is used. The illustrations and text may include optional equipment and accessories and may not include all standard equipment. Your Case dealer/distributor will be able to give you details of the products and their specifications available in your area.



**SAFETY™
NEVER HURTS**

Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs and use any safety features provided.

© 2005 CNH America LLC Case is a registered trademark of CNH America LLC
CNH Capital is a trademark of CNH America LLC
Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies. All rights reserved. Printed in U.S.A.