DESMOND EQUIPMENT S.A.







-Rugged -Reliable -Productive



ENGINE

Type: Caterpillar Model: 3126B **Aspiration:** Turbocharged Capacity: 7.2 Liters

Power: 186kW @ 2500 RPM Torque: 926Nm @ 1650 PRM

TRANSMISSION

Type: 7F Model: 6WG210 Gearing:

Constant mesh Counter shaft with internal drop box

Gears: Forward - 6 Reverse - 3

Speed: 70 Km/H Torque Converter: Single phase, 3 element, lock-up clutches effective

in all gears. Downshift protection

AXLES

Front: Desmond axle with self leveling Airbag suspension 6x6 Hypoid differential with final drive reduction

6x4 Non-drive 15 tonne

Rear: Desmond tandem drive free swinging walking beam

Hypoid differential with reduction in tandem. Diff lock standard

STEERING

Articulated

Steering angle - 35° either side

Load sensing, orbital controlled with Q-Amp 2 1/2 turns lock to lock

TYRES

Front/rear: 20.5 x 25 Radial

Heavy duty rodust frame front and rear with tube type oscillation, adjustable

ELECTRICS

Voltage: 24 Volt

2 x 12 Volt sealed type Battery: **Filtenator:** 24 Volt / 70 Amp

BRAKES

Front: Air operated S-cam failsafe

drum brakes

Air over hydraulic discbrakes Rear:

on all four wheels

Air operated failsafe disc brake Park Brake:

on transmission and front axle

CAR FEATURES

Fully adjustable weight compensating suspension seat with seat belt

Rubber mounted Interior dome light Windscreen wiper

without notice

Fully-enclosed and lockable

Rear cab night working lights

Trainer driver seat

838 Desmond Equipment SA reserves

EQUIPMENT

PORT SHEPSTONE HEAD OFFICE

Telephone: (039) 685-4100/1 Facsmile: (039) 685-4476 P.O. Box 111 Port Shepstone 4240

HYDRAULIC SYSTEM

Oil Capacity: 160 Liters

Pumps: Fixed displacement external gear pump

Working

Steering - 17 Mpa pressure:

Tipping - 5 Mpa Full flow filtration

SERVICE CAPACITIES

Cooling system: 50 Liters Engine Crankcase: 21 Liters Transmission: 18 Liters

Rear axle/

Differential: 20 Liters Tandems: 110 Liters (Each side) Diesel tank: 200 Liters

STANDARD EQUIPMENT

Tinted windows

- Rear view mirrors
- **Emergency braking**
- Full road ordinance lights
- Indicators
- Dashboard with full instrumentation
- Hinged belly plate under engine
- Front tow hooks
- Air cleaner service indicator
- Rear window gaurd
- Airconditioner
- Back-up alarm

OPTIONAL EQUIPMENT

Radio / Tape Light gaurds ■ Wheel mud flaps

Tachograph Bin liner kit

Engine monitoring system

OPERATING WEIGHTS

	Iure	Uross	<i>-uyiouu</i>
Front axle:	8420	12000	1720
Middle axle:	4830	13040	9140
Rear Axle:	4830	13040	9140
Total	18080	38080	20000

PNEUMATIC SYSTEM

Up:

Capacity: 80 Liters

120 Psi (8.1 Bar) Working pressure:

Unloader valve controlled Dual circuit system

TIPPING TIMES (approx.)

16 seconds



