



Shaping the Future Together

CLG375A

Skid Steer Loader

Bucket Capacity	0.65 yd ³ (0.5 m ³)
Rated Load	2100 lb (954 kg)
Operating Weight	7500 lb (3400 kg)
Net Power	76.8 hp (57.3 kW) @2400 rpm



LIUGONG CONSTRUCTION MACHINERY N.A., LLC

20823 Park Row
Katy, Texas 77449 USA

T: +1 281-579-8882

F: +1 281-579-8388

Info@liugongna.com

www.liugongna.com

Specifications

Basic Data

Operating weight	7500 lb (3400 kg)
Rated load	2100 lb (954 kg)
Static tipping load	4200 lb (1908 kg)
Boom breakout force	5180 lb (2350 kg)
Bucket breakout force	5900 lb (2680 kg)
Traveling speed	7.5 mph (12.1 km/h)

Engine

Model	Yanmar 4TNV98T-ZPLYS
Type	Water-cooled, 4-stroke cycle direct injection
Rated power	82.6 hp (61.6 kW) @2400 rpm
Net power	76.8 hp (57.3 kW) @2400 rpm
Peak torque	215.4 lbf (292.6 N.m)
Displacement	201in ³ (3.3 L)
Tier rating	EPA Tier III & Euro Stage III
Fuel tank capacity	21.1 gal (80 L)

Electrical

Battery	12-volt, 680CCA
Alternator	55 amp
Work-lights	2 front lights & 2 rear lights

Hydraulic System

Traveling hydrostatic pressure	4641 psi (32 MPa)		
Working hydraulic pressure	3000 psi (20.7 MPa)		
Flow	21 gal/min (79.2 L/min)		
High flow	31.7 gal/min (120.2 L/min)		
Hydraulic tank capacity	10.6 gal (40 L)		
Hydraulic cycle time (s)			
Raise	Dump	Lower (empty, float down)	Total
4.1	2.1	2.2	8.4

Tire

Tire size	12-16.5/ply
-----------	-------------

Working Range

Max. dump height	8' (2425 mm)
Reach @ max. dump height	22" (560 mm)
Dump angle @ max. dump height	39°
Rollback@ ground level	30°
Height to bucket hinge pin @ max. dump height	10'2" (3105 mm)
Ground clearance	8.3" (210 mm)
Angle of departure	27°
Front clearance radius	6'11" (2100 mm)

Standard Equipment

- Yanmar 4TNV98T engine
- Control safety interlock
- Enclosed ROPS/FOPS Cab + air conditioner
- Auxiliary high flow 31.7gal/min (120.2 L/min)
- Seat belt
- Prefilter
- General bucket 0.65yd³ (0.5m³)
- Boom interlock
- Alarm, back up
- Rotary beacon

Optional Equipment

- ▲ Open ROPS/FOPS cab
- ▲ Flow 21 gal/min (79.2 L/min)
- ▲ Tire chain
- ▲ Extinguisher
- ▲ Solid tire

Optional Attachment

- 4 in 1 bucket 0.52yd³ (0.4m³)
- Scrap bucket φ 14"-25.6" (350-650mm)
- Hydraulic hammer
- Fork
- Lift boom
- Auger
- Bale spear
- Rock bucket 0.52yd³ (0.4m³)
- Cold planer
- Snow blade
- Pick-up sweeper
- Backhoe
- Hydraulic shear

Dimensions (mm)

