

永州翊翔机电设备有限公司

YONG ZHOU YI XIANG MACHINERY & EQUIPMENT LTD.



YIXIANG
翊翔机电

GR215 平地机



GR 系列平地机主要技术参数 Specifications of GR Series Motor Grader

型 号 Model	GR165	GR180	GR200	GR215
基本参数 Basic specification				
发动机 Engine model	D6114ZGB	D6114ZGB	D6114ZGB	Cummins 6CT8.3-C215
额定功率 / 转速 Rated power/speed	125kW(170hp)/2200rpm	140kW(190hp)/2200rpm	147kW(200hp)/2200rpm	160kW(215hp)/2200rpm
整机外型尺寸(标配) Dimension(LxWxH)(Standard)	9242x2601x3430mm	9298x2601x3430mm	9298x2601x3430mm	9422x2601x3430mm
整机重量(标配) Operating weight (Standard)	15000kg	15400kg	16000kg	17000kg
前轮分配重量 Module Weight on front wheels	4500kg	4620kg	4800kg	5100kg
后轮分配重量 Module weight on rear wheels	10500kg	10780kg	11200kg	11900kg
轮胎规格 Tire size	17.5-25 RP12	17.5-25 RP12	17.5-25 RP12	17.5-25 RP12
最小离地间隙 Min. ground clearance	430mm	430mm	430mm	430mm
前后桥距 Distance between front and rear axles	6266mm	6266mm	6266mm	6266mm
中后轮距 Distance between middle and rear wheels	1639mm	1639mm	1639mm	1639mm
工作参数 Operating specification				
前轮最大转向角 Max. steering angle of front wheels	± 45°	± 45°	± 45°	± 45°
前轮最大倾斜角 Max. lean angle of front wheels	± 17°	± 17°	± 17°	± 17°
前桥最大摆动角 Max. oscillation angle of front axle	± 15°	± 15°	± 15°	± 15°
车架转向角 Frame articulation angle	± 25°	± 25°	± 25°	± 25°
最小转弯半径 Min. turning radius using articulation	7.8m	7.8m	7.8m	7.8m
最大提升高度 Maximum lift above ground	460mm	460mm	460mm	460mm
最大铲土深度 Maximum depth of cutting	500mm	500mm	500mm	500mm
铲刀 最大侧倾角度 Maximum blade position angle	90°	90°	90°	90°
切削角 Blade cutting angle	28°~70°	28°~70°	28°~70°	28°~70°
回转角 Circle reversing rotation	360°	360°	360°	360°
长度 x 弦高 Moldboard width x height	3965x610mm	3965x610mm	4270/3965x610mm	4270x610mm
性能参数 Performance specification				
前进速度 Travelling speed, forward	5, 8, 11, 19, 23, 38km/h	5, 8, 11, 19, 23, 38km/h	5, 8, 11, 19, 23, 38km/h	5, 8, 11, 19, 23, 38km/h
后退速度 Travelling speed, reverse	5, 11, 23km/h	5, 11, 23km/h	5, 11, 23km/h	5, 11, 23km/h
最大牵引力(f=0.75)Max. tractive force	77kN	80kN	82kN	87kN
最大爬坡能力 Max. gradeability	20°	20°	20°	20°

选装件 Optional Equipment

- 1) 自动找平装置 2) 前推土铲 3) 后松土器 4) 液压拔销器 5) 防翻滚驾驶室 6) 松土耙 7) 重型刀片 8) 破冰轮
 1. Automatic leveling Unit. 2. Front dozer. 3. Rear ripper. 4. Hydraulic pin controller of the swing frame 5. Rops cab. 6. Front ripper 7. Heavy duty blade 8. Ice breaker

注: 产品随技术进步将不断改进, 差异之处将在订货时说明。
 Under our policy of continuous product development and improvement, we reserve the right to change specifications and design without prior notice.



GR 系列平地机主要用于公路、机场、农田等大面积的地面平整和挖沟、刮坡、松土、除雪等作业, 该系列平地机性能先进、工作效率高、操作舒适, 关键部件采用国际化配套, 是国防工程、矿山建设、城乡道路等现代化施工的理想设备。

GR Series Motor Grader are mainly used in ground leveling, canalling, slop scraping, earth moving, scarification or snow removal work on road, airfield, farmland and so on. They have the advantages of advanced performance, high efficiency and comfortable operation. Many key components adopt international famous products to guarantee the quality. They are necessary construction machines for national defense engineering, mine construction, town and country roads building, and farmland improvement.

yi xiang

www.crane-china.com 翱翔机电

yi xiang 永州翱翔机电设备有限公司
YONG ZHOU YI XIANG MACHINERY & EQUIPMENT LTD.

地址:湖南省长沙市五一大道韭菜园路389号华美欧大厦2013-2014室
ADD: ROOM 2013-2014, HUAMEIOU BUILDING, NO. 389,
WUYI AVE, CHANGSHA, HUNAN, CHINA

邮址(E-mail): info@crane-china.com

总机(TEL): 86-731-85816117 82880555/666/777

传真(FAX): 86-731-85816217 82880111

电话(TEL): 86-746-8422780 8323288

传真(FAX): 86-746-8420289

地址:湖南省永州市冷水滩区湘永路129号中亚家园2104室
ADD: ROOM 2104, ZHONGYA JIAYUAN, NO. 129 XIANGYONG RD,
LENG SHUI TAN DISTRICT, YONGZHOU, HUNAN, CHINA