Bergmann Dumper 2030 hi swivel



Strong arguments for your advantage

- high stability thanks to oscillating axle
- ► hydraulical park brake
- instrument board lowerable and lockable
- type test approval by TBG

Advantages of Bergmann dumper:

- > TÜV and TBG approvals
- Movable parts made from chrome
- > Wide tyres for all models
- > Hydraulic park brakes
- > Ergonomic operator's stand
- Easy access to all maintanance and service points
- > Lowerable and lockable instrument board
- > Articulated steering / oscillating rear axle



Bergmann Dumper 2030 hi swivel

Technical Data

Weight/ bucket capacity	Payload	2.500 kg
	Unladen weight	2.340 kg
	Struck level	1.150 L
	Heaped	1,8 m ³
	Bucket system	hydraulically swivelling and tipping
		bucket by 180°
Dimensions	Total height with protection bar	2.780 mm
	Total height without protection bar	1.990 mm
	Total length	3.940 mm
	Total width	1.780 mm
	Tipping height	1.150 – 1.850 mm
	Ground clearance	246 mm
	Ground cicarance	240 111111
Transmission	Hydrostatic 4-wheel-drive	
Transmission		
	speed I: 0-10 km/h	
	speed II: 0-23 km/h	
Charina	The document and a color of the	
Steering	Hydraulic articulated steering acting	g over priority flow
	Steering angle 40° to each side	
Auto / Dustino	Front culo visid year culo assillation	stared / 12° maintanance from all
Axles / Brakes	Front axle rigid, rear axle oscillating stored +/- 12°, maintenance-free-bath multi-disc brake with automatic adjustment in the front axle,	
	hydraulically applicated locking bra	
	front and rear axle.	ke acting over articulated shart on
	ITOTIL ATTU TEAT AXIC.	
Engine	3 cylinder Kubota Diesel engine –wa	ater cooled-
Liigilic		n
Ligitic	Output power 25,5 KW at 2.800 rpn	n.
Liigine		n.
	Output power 25,5 KW at 2.800 rpn	n.
Tyres		n.
Tyres	Output power 25,5 KW at 2.800 rpn Standard, 11,5/80-15.3 AS Profil	n.
	Output power 25,5 KW at 2.800 rpn Standard, 11,5/80-15.3 AS Profil Fuel 50 L	n.
Tyres	Output power 25,5 KW at 2.800 rpn Standard, 11,5/80-15.3 AS Profil	n.
Tyres Tank capacity	Output power 25,5 KW at 2.800 rpn Standard, 11,5/80-15.3 AS Profil Fuel 50 L Hydraulic oil 40 L	
Tyres	Output power 25,5 KW at 2.800 rpm Standard, 11,5/80-15.3 AS Profil Fuel 50 L Hydraulic oil 40 L 12V electrical installation with main	n switch, control panel for engine
Tyres Tank capacity	Output power 25,5 KW at 2.800 rpn Standard, 11,5/80-15.3 AS Profil Fuel 50 L Hydraulic oil 40 L 12V electrical installation with main water temperature, fuel and service	n switch, control panel for engine hour meter, control lamps for motor
Tyres Tank capacity	Output power 25,5 KW at 2.800 rpm Standard, 11,5/80-15.3 AS Profil Fuel 50 L Hydraulic oil 40 L 12V electrical installation with mair water temperature, fuel and service oil; park brake, direction indicator, by	n switch, control panel for engine hour meter, control lamps for motor
Tyres Tank capacity	Output power 25,5 KW at 2.800 rpn Standard, 11,5/80-15.3 AS Profil Fuel 50 L Hydraulic oil 40 L 12V electrical installation with main water temperature, fuel and service	n switch, control panel for engine hour meter, control lamps for motor
Tyres Tank capacity Electrics	Output power 25,5 KW at 2.800 rpm Standard, 11,5/80-15.3 AS Profil Fuel 50 L Hydraulic oil 40 L 12V electrical installation with mair water temperature, fuel and service oil; park brake, direction indicator, brilter, display for drive position	n switch, control panel for engine hour meter, control lamps for motor pattery charging control, hydraulic
Tyres Tank capacity	Output power 25,5 KW at 2.800 rpm Standard, 11,5/80-15.3 AS Profil Fuel 50 L Hydraulic oil 40 L 12V electrical installation with mair water temperature, fuel and service oil; park brake, direction indicator, brilter, display for drive position Hydro sprung seat adjustable and co	n switch, control panel for engine hour meter, control lamps for motor pattery charging control, hydraulic ollapsible, instrument panel lowerable
Tyres Tank capacity Electrics	Output power 25,5 KW at 2.800 rpm Standard, 11,5/80-15.3 AS Profil Fuel 50 L Hydraulic oil 40 L 12V electrical installation with mair water temperature, fuel and service oil; park brake, direction indicator, brilter, display for drive position Hydro sprung seat adjustable and cand lockable with ignition key, tow-	n switch, control panel for engine hour meter, control lamps for motor pattery charging control, hydraulic ollapsible, instrument panel lowerable bar coupling, lighting system
Tyres Tank capacity Electrics	Output power 25,5 KW at 2.800 rpm Standard, 11,5/80-15.3 AS Profil Fuel 50 L Hydraulic oil 40 L 12V electrical installation with main water temperature, fuel and service oil; park brake, direction indicator, be filter, display for drive position Hydro sprung seat adjustable and count and lockable with ignition key, towaccording to German traffic regulates.	n switch, control panel for engine hour meter, control lamps for motor pattery charging control, hydraulic ollapsible, instrument panel lowerable
Tyres Tank capacity Electrics	Output power 25,5 KW at 2.800 rpm Standard, 11,5/80-15.3 AS Profil Fuel 50 L Hydraulic oil 40 L 12V electrical installation with main water temperature, fuel and service oil; park brake, direction indicator, be filter, display for drive position Hydro sprung seat adjustable and count and lockable with ignition key, towaccording to German traffic regulating grain steel,	n switch, control panel for engine hour meter, control lamps for motor pattery charging control, hydraulic ollapsible, instrument panel lowerable bar coupling, lighting system cions, bucket from abrasion-proof fine-
Tyres Tank capacity Electrics	Output power 25,5 KW at 2.800 rpm Standard, 11,5/80-15.3 AS Profil Fuel 50 L Hydraulic oil 40 L 12V electrical installation with main water temperature, fuel and service oil; park brake, direction indicator, be filter, display for drive position Hydro sprung seat adjustable and count and lockable with ignition key, towaccording to German traffic regulating grain steel,	n switch, control panel for engine hour meter, control lamps for motor pattery charging control, hydraulic ollapsible, instrument panel lowerable bar coupling, lighting system