Zettelneuer

Backhoe Attachment for Articulated Loader ZL 501







The operator's stand is ideally suited for quick and comfortable work. Working area more than 36 \mbox{m}^2 (388 sq.ft.).



The ZL 501 with backhoe attachment in transport position, ready to roll to the next site. Fully equipped for travel on public roads.

This small and powerful backhoe is ideally suited for medium-sized construction sites and landscaping.


Only two easily attached mounting plates and additional hydraulic connections are needed to prepare the ZL 501 for quick and simple attachment of the backhoe. All that needs to be done then is to connect the hydraulic couplings and hook the backhoe in place. Two hydraulic supports assure stability at any gradient.

For work in tight places, for instance alongside walls, the operator can slide the backhoe sideways by as much as 1.10 m (3'7") without leaving his seat.





ldeal for any kind of work: extreme reach and dump height. The operator can slide the backhoe sideways by up to 1.10 m (3'7") without leaving his seat.



Technical data	Bucket arm 1200 mm (3'11")	Bucket arm 1500 mm (4'11")
Digging depth	2350 mm	2650 mm
922 B	(7'9")	(8'8")
Maximum reach	4550 mm	4830 mm
D	(14'11")	(15′10″)
Dump height	2950 mm	3050 mm
Transport height	(9'8")	(10')
Transport height	3170 mm (10'5")	
Pulling force of bucket arm	1420 kp	1100 kp
Fulling force of bucket arm	(3192 lbs)	(2473 lbs)
Capacity at max. reach	600 kp	500 kp
Capacity at max. reach	(1349 lbs)	(1124 lbs)
Breakout force vertical to bucket	5600 kp	(1121100)
	(12589 lbs)	
Working range of bucket	177°	
Working range of jib	200°	
Lateral displacement	1100 mm	
zatora: disprasorment	(3'7")	
Total width	1410 mm	
	(4'8")	
Hydraulic operating pressure	160 bar	
	(2275 psi)	
Hydraulic rate of flow	30-36 I/min	
a n v		JS; 6.6-7.7 gal Imp.)
Power required	15-18 HP	
Operating weight without buckets	735 kg	750 kg
	(1620 lbs)	(1653 lbs)
Buckets	Width	Capacity
Bucket with scraper	280 mm	.05 m ³
Buoket Will Scraper	(11")	(1.8 cu. ft)
Bucket	450 mm	.07 m ³
	(1'6")	(2.5 cu. ft)
Bucket	600 mm	.1 m ³
	(2')	(3.5 cu. ft)
Ditch cleaning scoop	1200 mm	
5 1	(3'11")	
Hydraulic clamshell grab		.1 m ³
		(3.5 cu. ft)



Zettelmeyer

A member of the IBH Group

Zettelmeyer Maschinenfabrik GmbH P.O.B. 1340 D-5503 Konz/Trier, W.-Germany Tel. (0 65 01) 8 40, Tx. 0472771

Distributor		